



SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

WD-40

Date of issue: 2006-06-29

Revision date: 2024-07-22

Version: 30

1. IDENTIFICATION

A. Product name

- WD-40

B. Recommended use and restriction on use

- General use : Lubracants, Corrosion inhibitor, Washing and cleaning products
- Application of the substance / the mixture : Lubricants, Anti-rust oil
- Restriction on use : No further relevant information available.

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : BEX Inter corporation Ltd.
- Address : 7-15, Baumoe-ro 27-gil, Seocho-gu, Seoul, KOREA
- Emergency telephone number : TEL +82-2-571-4040, FAX +82-2-575-1336

○ Supplier/Distributor information

- Company name : BEX Inter corporation Ltd.
- Address : 7-15, Baumoe-ro 27-gil, Seocho-gu, Seoul, KOREA
- Emergency telephone number : TEL +82-2-571-4040, FAX +82-2-575-1336

2. HAZARD IDENTIFICATION

A. GHS Classification

- Aerosols : Category1
- Skin corrosion/irritation : Category2
- Germ cell mutagenicity : Category1B
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
- Aspiration hazard : Category1

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

○ Hazard statements

- H222 Extremely flammable aerosol
- H229 Pressurised container: May burst if heated
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H336 May cause drowsiness and dizziness.
- H340 May cause genetic defects

○ Precautionary statements

1) Prevention

- P201 Obtain special instructions before use.

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment (if in eyes, wash with plenty of running water; if in contact with skin, wash with plenty of running water; if inhaled, move to fresh air; if ingested, seek medical advice on whether to induce vomiting).
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash before reuse.

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | Trade names and Synonyms | CAS No. | Content(%) |
|--|--|--|------------|
| Distillates (petroleum), hydrotreated light | Deodorized kerosene ; Low odor paraffinic solvent | 64742-47-8 | 40 ~ 50 |
| Distillates (petroleum), hydrotreated heavy paraffinic | Emulsifiable oil | 64742-54-7 | 10 ~ 20 |
| Propane | Dimethylmethane ; Propyl hydride ; n-Propane ; Propyldihydride ; | 74-98-6 | 16 ~ 21 |
| Butane | N-Butane ; Butyl hydride ; Methylethylmethane ; | 106-97-8 | 10 ~ 14 |
| Alkane(C=1~5)oic acid Substituted Alkyl(C=2~4)Alkyl(C=6~10) ester Alkali metal salt | Not available | closed Approval number T-2022-00785 (expiration date : 2027-12-19) | 1 ~ 4 |
| Fatty acids, (C=15~20)-unsatd., dimers | Not available | | 1 ~ 4 |
| Alkyl(C=1~3) alkyl(C=1~5) Carbomonocyclic alcohol | Not available | | 0.01 ~ 1 |

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Get medical attention immediately.

- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.
- Get medical attention immediately.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Causes skin irritation
- Extremely flammable aerosol
- May be fatal if swallowed and enters airways
- May cause drowsiness and dizziness.
- May cause genetic defects

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.

- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- **ACGIH TLV**
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : TWA 5 mg/m³, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
 - [Propane] : Asphyxia
 - [Butane] : STEL 1000 ppm
- **OSHA PEL**
 - [Propane] : 1000 ppm, 1800 mg/m³

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

- **Respiratory protection**
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Consider warning properties before use.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- **Eye protection**
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- **Hand protection**
 - Wear appropriate chemical resistant glove.
- **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------|--|
| A. Appearance | |
|---------------|--|

| | |
|---|---|
| - Appearance | Liquid |
| - Color | Light Yellow |
| B. Odor | Characteristic |
| C. Odor threshold | Not available |
| D. pH | Not available |
| E. Melting point/Freezing point | Not available |
| F. Initial Boiling Point/Boiling Ranges | 147 ~ 663°C (undiluted solution) |
| G. Flash point | 79.5°C (undiluted solution) |
| H. Evaporation rate | Not available |
| I. Flammability(solid, gas) | flammable gas |
| J. Upper/Lower Flammability or explosive limits | 5.0 / 0.6 (undiluted solution, (Distillates (petroleum), hydrotreated light)) |
| K. Vapour pressure | 0.023kPa at 20°C (undiluted solution) |
| L. Solubility | insoluble in water |
| M. Vapour density | 6.2 (undiluted solution) |
| N. Specific gravity(Relative density) | Not available |
| O. Partition coefficient of n-octanol/water | Not available |
| P. Autoignition temperature | 239°C (undiluted solution) |
| Q. Decomposition temperature | Not available |
| R. Viscosity | 3.72mm ² /s at 40°C (undiluted solution) |
| S. Molecular weight | Not available |

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- Respiratory tracts**
 - May be fatal if swallowed and enters airways
- Oral**
 - Not available
- Eye-Skin**
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity**
 - * **Oral**
 - Product (ATEmix) : >5000mg/kg
 - [Distillates (petroleum), hydrotreated light] : LD50 > 5000 mg/kg Rat (OECD TG 420, GLP) (Read-across CAS No. 68333-23-3) (ECHA)
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rat (Read-across CAS No. 64742-56-9) (OECD TG 401, GLP) (ECHA)
 - * **Dermal**

- Product (ATEmix) : >5000mg/kg
- [Distillates (petroleum), hydrotreated light] : LD50 > 2000 mg/kg Rabbit Not classified (OECD TG 402, GLP) (Read-across CAS No. 68333-23-3) (ECHA)
- [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rabbit (Read-across CAS No. 64742-56-9) (OECD TG 402, GLP) (ECHA)
- * **Inhalation**
 - Product (ATEmix) : 20.0mg/L < ATEmix <= 50.0mg/L, Vapour, 4hr
 - [Distillates (petroleum), hydrotreated light] : Vapor LC50 > 5.28 mg/L 4 hr No death Not classified (OECD TG 403, GLP) (Read-across CAS No. 8008-20-6) (ECHA)
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : Aerosol LC50 > 5.53 mg/L 4 hr Rat (Read-across CAS No. 64741-88-4) (OECD TG 403) (ECHA)
 - [Propane] : Gas LC50 > 38890 ppm 4 hr (> 55000 ppm 2 hr) Guinea pig (NITE)
 - [Butane] : Gas LC50 > 200000ppm 4 hr Rat Not classified (800000ppm 15 min) (Read-across 74-98-6) (ECHA)
- **Skin corrosion/irritation**
 - Causes skin irritation
- **Serious eye damage/irritation**
 - Not available
- **Respiratory sensitization**
 - Not available
- **Skin sensitization**
 - Not available
- **Carcinogenicity**
 - * **IARC**
 - Not available
 - * **OSHA**
 - Not available
 - * **ACGIH**
 - Not available
 - * **NTP**
 - Not available
 - * **EU CLP**
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : Not available
 - [Butane] : Carc.1A (butane (containing ≥ 0.1% butadiene (203-450-8)))
- **Germ cell mutagenicity**
 - May cause genetic defects
- **Reproductive toxicity**
 - Not available
- **STOT-single exposure**
 - May cause drowsiness and dizziness.
- **STOT-repeated exposure**
 - Not available
- **Aspiration hazard**
 - May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- **Fish**
 - [Distillates (petroleum), hydrotreated light] : LL50 2 ~ 5 mg/L 96 hr Oncorhynchus mykiss (OECD TG 203, GLP) (ECHA)
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : LL50 > 100 mg/L 96 hr Pimephales promelas (Read-across) (OECD TG 203, GLP) (ECHA)
- **Crustaceans**
 - [Distillates (petroleum), hydrotreated light] : EL50 1.4 mg/L 48 hr Daphnia magna (OECD TG 202, GLP) (ECHA)
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : EL50 > 10000 mg/L 48 hr Daphnia magna (Read-across), NOEL 10 mg/L 21 d Daphnia magna (Read-across 64742-53-6) (OECD TG 211, GLP) (ECHA) (ECHA)
- **Algae**
 - [Distillates (petroleum), hydrotreated light] : EL50 1 ~ 3 mg/L 48 hr Raphidocelis subcapitata (OECD TG 201, GLP) (ECHA)

- [Distillates (petroleum), hydrotreated heavy paraffinic] : NOEL > 100 mg/L 72 hr (Read-across CAS No. 72623-87-1) (OECD TG 201) (ECHA)

B. Persistence and degradability

○ Persistence

- [Butane] : log Pow 2.31 (ECHA)

○ Degradability

- Not available

C. Bioaccumulative potential

○ Bioaccumulative potential

- [Distillates (petroleum), hydrotreated light] : BCF 130 ~ 159 (Jordanella floridae(Fish, fresh water), 1mg/l) (IUCLID)

○ Biodegradation

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not readily biodegradable, 31 % 28 d (O₂ consumption) (Read-across) (OECD TG 301 F, GLP) (ECHA)

- [Butane] : Readily biodegradable, 100 % 385.5 hr (test mat. Analysis) (Read across 74-84-0) (ECHA)

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration

- Oil water separation technology shall be applied as pre-waste treatment if it is applicable

- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

- Will be pre-processed by the separation of oil and water.

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act

- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1950

B. Proper shipping name

- AEROSOLS

C. Hazard Class

- 2.1

D. IMDG CODE/IATA DGR Packing group

- Not applicable

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.

- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.

- EmS FIRE SCHEDULE : F-D (Flammable gases)

- EmS SPILLAGE SCHEDULE : S-U (Gases (flammable, toxic or corrosive))

15. REGULATORY INFORMATION

A. National and/or international regulatory information

POPs Management Law

- [Distillates (petroleum), hydrotreated light] : Not applicable
- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not applicable
- [Propane] : Not applicable
- [Butane] : Not applicable
- [Alkane(C=1~5)oic acid Substituted Alkyl(C=2~4)Alkyl(C=6~10) ester Alkali metal salt] : Not applicable
- [Fatty acids, (C=15~20)-unsatd., dimers] : Not applicable
- [Alkyl(C=1~3) alkyl(C=1~5) Carbomonocyclic alcohol] : Not applicable

Information of EU Classification

* Classification

- [Distillates (petroleum), hydrotreated light] : H304
- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not applicable
- [Propane] : H220,H280
- [Butane] : H220,H280,H340

U.S. Federal regulations

* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable

* CERCLA Section 103 (40CFR302.4)

- Not applicable

* EPCRA Section 302 (40CFR355.30)

- Not applicable

* EPCRA Section 304 (40CFR355.40)

- Not applicable

* EPCRA Section 313 (40CFR372.65)

- Not applicable

Rotterdam Convention listed ingredients

- Not applicable

Stockholm Convention listed ingredients

- Not applicable

Montreal Protocol listed ingredients

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2006-06-29

C. Revision number and Last date revised

- 30 times, 2024-07-22

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).